



ISO 9001 CERTIFIED

RISLONE TECHNICAL BULLETIN

Tech Bulletin #: TB-41150-1

Page 1 of 1

Date 1st Issued: 27 February 2013

Date Revised: 23 July, 2013

Rislone Cooling System Repair

Part #: 41150

COOLING SYSTEM REPAIR

Rislone® Cooling System Repair has twice the performance of other products by not only stopping cooling system leaks, but adding future protection. It is scientifically formulated to stop coolant leaks, thereby reducing antifreeze loss, while correcting other cooling system problems helping to prevent costly repairs and breakdowns. In addition, Cooling System Repair contains Xtreme Cool™ which stops overheating and reduces water temperature. Works on all 4, 6, 8, and 10 cylinder vehicles and in any petrol, LPG, turbocharged and diesel engines. Use with ALL types and colors of 50-50 mix antifreeze coolant and / or water. For most vehicles leaks stop instantly. For many vehicles, this is your last chance before paying an expensive repair bill or replacing the vehicle.

Twice the Performance

Formula A

Stops & Prevents Leaks with:

- Carbon Fiber Sealer
- Leak Sealing Liquid
- Stop leak Treatment

Formula B

Add Protection with:

- Water Pump Lube
- Corrosion Inhibitors
- Heat Transfer Agent

XTREME COOL™

Xtreme Cool™ reduces the surface tension of coolant increasing the wetting ability. This improves heat transfer reducing coolant temperature helping to prevent overheating and leaks.

DANGER: Opening the cooling system while the engine is hot or running may cause severe burns.

NOTE: Cooling systems that are dirty or partially clogged should be flushed before usage. Protect from freezing.

INSTRUCTIONS:

Install only in a cold engine. Shake well. Pour entire contents of the 2-chamber bottle directly into the radiator. If direct access to radiator is not available, install in overflow tank. Fill radiator overflow tank to proper level and reinstall cap. Drive/idle engine for 15 minutes. If leak continues, second application may be required or mechanical attention is needed. Leave Cooling System Repair in cooling system for continued protection.



| | |
|--------------------|----------------------|
| Part Number: | 41150 |
| UPC Item: | 0 78615 41150 4 |
| UPC Case: | 1 00 78615 41150 1 |
| Bottle Contents: | 500 mL |
| Bottle Size (cm): | 9.1 x 4.6 x 21.3 |
| Bottle Cube: | 892 |
| Case Pack: | 4 bottles |
| Case Size (cm): | 18.8 x 9.9 x 22.6 |
| Case Cube: | 4206 |
| Case Weight (kg): | 2.4 |
| Pallet: | TI 60 HI 5 Total 300 |
| Pallet Height (m): | 1.3 |

DOSAGE

1 bottle treats systems up to 16 litres.