



ISO 9001 CERTIFIED

RISLONE TECHNICAL BULLETIN

Tech Bulletin #: TB-44416-2

Page 1 of 1

Date 1st Issued: 27 February 2013

Date Revised: December 2, 2014

Rislone Ring Seal Smoke Repair

Part #: 44416

RING SEAL SMOKE REPAIR

Rislone® Ring Seal® is formulated to help stop blue exhaust smoke, reduce oil burning and prevent plug fouling caused by “blow-by”. Blow-by is usually caused by gaps in internal engine parts resulting from excess wear. Ring Seal contains viscosity improvers that thicken the oil film filling these gaps.

- Contains high-shear polymers which provide a seal for worn pistons & rings to stop blow-by.
- Cushions and coats engine parts helping to reduce wear and quiet noisy lifters.
- Stops blue exhaust smoke and reduces oil burning.
- Retains oil flow characteristics in hot and cold weather.
- Works on all 4, 6, and 8 cylinder vehicles.
- Use on any gasoline or diesel engines.
- Works with conventional, high kilometre and synthetic engine oils.
- Add to engine oil anytime.
- Protecting engines since 1921.



TEST	ASTM	TYPICAL PROPERTIES
Specific Gravity @ 15.6°C	D-1298	0.85 to 0.87
API Gravity	D-1298	35
Flash Point PMCC	D-93	180°C
Viscosity, cSt. @ 100°C	D-445	420 - 480
Pour Point °C	D-97	-15°C to -25°C

INSTRUCTIONS:

Add entire bottle of **Ring Seal Smoke Repair** to engine crankcase at or between oil changes. Idle or drive engine for 5 minutes after installation.

Add Ring Seal Smoke Repair every 3500 km or with every oil change.

If smoke continues, second application may be required or mechanical attention is needed.

Part Number:	44416
UPC Item:	0 78615 44416 8
UPC Case:	1 00 78615 44416 5
Bottle Size:	473 mL
Bottle Size (cm):	8,9 x 5,1 x 19,3
Bottle Cube:	876
Case Pack:	6 bottles
Case Size (cm):	18,6 x 16,4 x 20,5
Case Cube:	6,253
Case Weight (kg):	3
Pallet:	TI 38 HI 6 Total 228
Pallet Height (cm):	135

DOSAGE:

One bottle treats 4 to 6 liters of oil for regular 4, 6 and 8 cylinder engines. For larger engines, use 1 bottle for every 5 liters of capacity. On 4-Stroke ATV, Motorcycle and small engines, including wet clutch applications, use approximately 100 mL per liter of oil capacity.