

 ISO 9001 CERTIFIED	RISLONE TECHNICAL BULLETIN	
	Tech Bulletin #: TB-44629-0	Page 1 of 1
	Date 1 st Issued: 20 July, 2015	Date Revised: n/a
	Rislone Power Steering Stop Leak Concentrate	Part 44629

POWER STEERING STOP LEAK CONCENTRATE

Rislone Power Steering Stop Leak Concentrate is specially designed to stop seal and o-ring leaks caused by normal power steering wear and age. Works on rack & pinion units, gear boxes and pumps. Keeps power steering seals soft and pliable. Non-corrosive, non-clogging and non-foaming.

Works with ALL domestic, import and heavy duty power steering fluid; including petroleum, mineral oil, synthetics and ATF automatic transmission fluid.

- Stops & Seals Steering Fluid Leaks
- Restores O-rings & Seals to Stop & Prevent Steering Leaks



INSTRUCTIONS:

Add Stop Leak to power steering reservoir to restore fluid level. Do not overfill. Leaks usually stop in 300 km or 3 days of driving. If leak continues, a second application may be required or mechanical attention is needed.

DOSAGE:

One bottle treats up to 2,5 liters of fluid. For larger systems, use 1 bottle for every 2 liters of fluid capacity.

Part Number:	44629
UPC Item:	0 78615 44629 2
UPC Case:	1 00 78615 44629 9
Bottle Size:	325 mL
Bottle Size (cm):	7,6 x 4,6 x 16,5
Bottle Cube:	577
Case Pack:	6 bottles
Case Size:	15,7 x 14 x 17,5
Case Cube:	3846
Case Weight (kg):	2,1
Pallet:	TI 48 HI 7 Total 336
Pallet Height (cm):	163